



PRE CONDITIONED AIR (PCA)

KEY FEATURES

- Seamless copper tubing implemented on all refrigeration circuits
- Full UL listing on all standard units offered
- Compliance with 100% Buy American requirements
- Fully removable panels for simplified maintenance
- Dual powdercoat process on frames and panels
- Rear or top discharge condenser fans.
- VFD controlled blower, compressor and condenser fans for increased efficiency.
- Robust coil enhancements

480V /60HZ /3 PHASE

	PCAB030	PCAB045	PCAB060	PCAB090	PCA120
NOMINAL TONS	30	45	60	90	120
HEAT	60 kW	80 kW	100 kW	160 kW	160 kW
AIR FLOW	180 PPM	250 PPM	325 PPM	500 PPM	525 PPM
STATIC PRESSURE	20"	25"	30"	35"	37"
BREAKER SIZE	100 AMP	150 AMP	200 AMP	300 AMP	350 AMP
POWER OPTIONS	480V/60Hz/3Phase — 575V/60Hz/3Phase 380V/50Hz/3Phase — 380V/60Hz/3Phase				
WEIGHT	3750 LBS	4250 LBS	5500 LBS	8300 LBS	9300 LBS
LENGTH	118"	124"	144"	150"	204"
WIDTH	88"	88"	88"	88"	90"
HEIGHT	44"	54"	61"	62"	73"

UL & ULC Listed | RAL 9003 Powdercoat | R410 A Refrigerant

